Power PCB Relay RT1

- **1 pole 12A/16A, 1 form C (CO) or 1 form A (NO) contact**
- **DC or AC coil**
- **5kV/10mm coil-contact, reinforced insulation**
- **Ambient temperature 85°C (DC coil)**
- **WG version: product in accordance to IEC 60335-1**
- **Reflow version: for THR (Through-Hole Reflow) soldering process**

F0144-C

Typical applications
Boiler control, timers, garage door control, POS automation, interface modules

Approvals

VDE REG.-Nr. 6106, cULus E214025, cCSAus 14385; CQC

Technical data of approved types on request

Contact Data

	12A	16A
Contact arrangement	1 form C (CO) or 1 form A (NO)	
Rated voltage	250VAC	
Max. switching voltage	400VAC	
Rated current	12A	16A
Limiting continuous current	12A	16A, UL: 20A
Limiting making current max. 4s, duty factor 10%	25A	30A
Breaking capacity max.	3000VA	4000VA
Contact material	AgNi 90/10, AgNi 90/10 gold plated	
Frequency of operation, with/without load		
DC coil	360/72000h^{-1}	
AC coil	360/36000h^{-1}	
Operate/release time max., DC coil	8/6ms	
Bounce time max., DC coil, form A/form B	4/6ms	
Electrical endurance	see electrical endurance graph[1)]	

Contact ratings

Type	Contact	Load	Cycles
IEC 61810			
RT314 DC-coil	A (NO)	16A, 250VAC, cosφ=1, 85°C	30x10^3
RT314 DC-coil	C (CO)	16A, 250VAC, cosφ=1, 85°C	10x10^3
RT314 DC-coil	A (NO)	10A, 400VAC, cosφ=1, 85°C	150x10^3
RT114 DC-coil	A (NO)	12A, 250VAC, cosφ=1, 85°C	50x10^3
RT114 AC-coil	A (NO)	12A, 250VAC, cosφ=1, 70°C	100x10^3
UL 508			
RT314	A/B (NO/NC)	20A, 250VAC, general purpose, 85°C	6x10^3
RT334	A (NO)	16A, 250VAC, gen. purpose, 85°C	50x10^3
RT314	A (NO)	1hp, 240VAC, 40°C	1x10^3
RT314	A (NO)	FLA/LRA, 4.5/13.1A, 480VAC, 70°C	100x10^3
EN60947-5-1			
RT314 DC-coil	A/B (NO/NC)	2A, 24VDC, DC13	6.050
EN60730-1			
RT314 DC-coil	A (NO)	12(2)A, 250VAC, 85°C	100x10^3

1) For reflow solderable versions: actual contact performance may be influenced by the reflow soldering process.

Max. DC load breaking capacity



Electrical endurance



Contact Data (continued)

Mechanical endurance	
DC coil	>30x10^6 operations
AC coil	>10x10^6 operations
AC coil, reflow version	>5x10^6 operations

Coil Data

Coil voltage range, DC coil/ AC coil	5 to 110VDC / 24 to 230VAC
Operative range, IEC 61810	2
Coil insulation system according UL	class F

Coil versions, DC coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%[2)]	Rated coil power mW
005	5	3.5	0.5	62	403
006	6	4.2	0.6	90	400
009	9	6.3	0.9	200	400
012	12	8.4	1.2	360	400
024	24	16.8	2.4	1440	400
048	48	33.6	4.8	5520	417
060	60	42.0	6.0	8570[2)]	420
110	110	77.0	11.0	28800[2)]	420

2) Coil resistance ±12%.
All figures are given for coil without pre-energization, at ambient temperature +23°C.
Other coil voltages on request.

Coil versions, AC coil 50/60 Hz

Coil code	Rated voltage VAC	Operate voltage VAC	Release voltage VAC	Coil resistance Ω±15%[3)]	Rated coil power VA
524	24	18.0	3.6	350[3)]	0.76
615	115	86.3	17.3	8100	0.76
620	120	90.0	18.0	8800	0.75
700	200	150.0	30.0	24350	0.76
730	230	172.5	34.5	32500	0.74

3) Coil resistance ±10%.
All figures are given for coil without pre-energization, at ambient temperature +23°C, 50 Hz.
Other coil voltages on request.

Coil operating range DC



Coil operating range AC



07-2012, Rev. 0712
www.te.com
© 2011 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Power PCB Relay RT1 (Continued)

Dimensions

THT version



THR version (reflow solderable)



Process conditions for Reflow soldering
according to EN61760-1





Product code structure

Typical product code: **RT 3 1 4 024**

Type
- **RT** Power PCB Relay RT1

Version
- **1** 12A, pinning 3.5mm, flux proof
- **2** 12A, pinning 5mm, flux proof *)
- **3** 16A, pinning 5mm, flux proof
- **B** 12A, pinning 3.5mm, wash tight
- **D** 16A, pinning 5mm, wash tight

Contact arrangement
- **1** 1 form C (CO) contact
- **3** 1 form A (NO) contact

Contact material
- **4** AgNi 90/10
- **5** AgNi 90/10 gold plated (for type RT31.)

Coil
- Coil code: please refer to coil versions table

Version
- **Blank** Standard version
- **WG** Product in accordance with IEC 60335-1 (domestic appliances)
- **R** Reflow solderable

*) Wash tight version on request

07-2012, Rev. 0712
www.te.com
© 2011 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Power PCB Relay RT1 (Continued)

Product code	Version	Contacts	Contact material	Coil	Version	Part number
RT114009	12A, pinning 3.5mm,	1 form C (CO)	AgNi 90/10	9VDC	Standard	1393239-9
RT114012	flux proof	contact		12VDC		1419108-1
RT114012WG					IEC60335-1 compliant	7-1415538-6
RT114024				24VDC	Standard	1-1393239-3
RT114024WG					IEC60335-1 compliant	1415539-4
RT114730				230VAC	Standard	1-1393239-9
RT115024			AgNi 90/10 gold pl.	24VDC		2-1393239-1
RT134012		1 form A (NO)	AgNi 90/10	12VDC		2-1393239-6
RT134024		contact		24VDC		3-1393239-0
RT214012	12A, pinning 5mm,	1 form C (CO)		12VDC		5-1393239-4
RT214024	flux proof	contact		24VDC		5-1393239-5
RT214524				24VAC		5-1393239-9
RT214730				230VAC		1419108-6
RT314005	16A, pinning 5mm,			5VDC		9-1393239-1
RT314006	flux proof			6VDC		9-1393239-3
RT314012				12VDC		9-1393239-5
RT314012WG					IEC60335-1 compliant	8-1415535-6
RT314024				24VDC	Standard	9-1393239-8
RT314024WG					IEC60335-1 compliant	1415538-7
RT314048				48VDC	Standard	1393240-1
RT314730				230VAC		1393240-7
RT315024			AgNi 90/10 gold pl.	24VDC		1-1393240-4
RT334009WG		1 form A (NO)	AgNi 90/10	9VDC	IEC60335-1 compliant	3-1415538-1
RT334012		contact		12VDC	Standard	4-1393240-5
RT334012WG					IEC60335-1 compliant	1-1415527-1
RT334024				24VDC	Standard	4-1393240-8
RT334048				48VDC		5-1393240-0
RTB14005	12A, pinning 3.5mm,	1 form C (CO)		5VDC		1-1393238-2
RTB14012	wash tight	contact		12VDC		1-1393238-5
RTB14024				24VDC		1-1393238-9
RTB14524				24VAC		2-1393238-4
RTD14005	16A, pinning 5mm,			5VDC		5-1393238-9
RTD14012	wash tight			12VDC		6-1393238-2
RTD14024				24VDC		6-1393238-8
RTD14048				48VAC		6-1393238-9
RTD34012		1 form A (NO)		12VDC		3-1419108-5
RTD34024		contact		24VDC		3-1419108-8

This list represents the most common types and does not show all variants covered by this datasheet.
Other types on request

07-2012, Rev. 0712
www.te.com
© 2011 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.